

Computer Servo Tensile Strength Test Equipment HTP-150B



Description:

This universal tensile machine can do various tensile testing in the field of rubber, leather products, plastics, chipboards, foam, plastic, film, flexible packaging, pipes, textiles, fibers, nanomaterials, polymers, composite materials, synthetic materials, packaging, paper, wire and cable, fiber optic cable, wirecables, seat belt, seat belt, leather belt, shoes, tape, polymer, copper, spring steel wire, stainless steel, castings, brass, non-ferrous metals, car parts, alloys and other non-metallic materials and metallic materials tensile, compression, bending, tearing, and 90 ° peel, 180 ° peel, shear adhesion, pull-out strength, an extension of the elongation test.

Applications:

Computer software to set speed, the load fracture (rupture), the running time, especially with the manual operation box: convenient calibration and fitted to hold the specimen positioning

Automatically determine the fracture of materials, when crushing it is automatic shutdown and automatically return

Curve types: curve longitudinal; The horizontal axis can be arbitrarily set.

The load to displacement; the load to time; displacement to time. Stress to strain; strain to time; stress to time.



Dongguan Hust Tony Instruments Co.,Ltd

东莞华科东尼仪器有限公司

Addr: No. 1 Tech 9 Road, High-New Tech Development Zone, Songshan Lake, Dongguan City 523808,China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: sale@tonyhk.hk

Technical parameters:

Model	HTP-150B
Maximum force capacity	15000kg (150KN) load cell for push and pull, 0.4%~100%(0.5)
Force measurement accuracy	within 0.5%
Test stroke	800mm, effective test width: 400 mm, or specified per customer
Test force loading the measuring range	0.4% -100% FS
Resolution	maximum test force of 1/200000
Test speed	0.01 - 500mm / min. or specified per customer.
Displacement measurement accuracy	± 0.5% of indication
Test force control rate adjustment range	0.05% -5% FS / S
Control accuracy	± 0.5% when the control rate \geq 0.05% FS / S
Machine size	1100*700*2100mm(L*W*H)
Dynamic system	servo motor + high precision ball screw
Power	220V/50HZ,4.4KW
Accessories	1 no Load cell, standard grips, operation software, English manual books and Video.
Net Weight	520kg, Gross weight:600 kg (after wooden package)
Package of strong wooden box size	118cm*80cm*230cm

Features:

- 1, high-precision: $\pm 0.5\%$, high-resolution: 1/200000;
- 2, selectable programmable control: to achieve loop control of load, position, deformation, and time;
- 3, real-time acquisition, refresh curve and record test data, a variety of Report print Output;
- 4, can be used for the retention test (Constant);
- 5, can be used for products of low cycle (repeatedly) fatigue test;
- 6, the unit of force values: N, KN, Kgf, Lbf, unit of length: mm, cm, in freely convertible

Applicable standards:



Dongguan Hust Tony Instruments Co.,Ltd

东莞华科东尼仪器有限公司

Addr: No. 1 Tech 9 Road, High-New Tech Development Zone, Songshan Lake, Dongguan City 523808,China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: sale@tonyhk.hk

ASTM D751,ASTM D882,ASTM D1117,ASTM D1445,ASTM D1593,ASTM D1683,ASTM D2209,ASTM D5034,ASTM D5053,ASTM D1424,ASTM D2212,ASTM D2262,ASTM D2261,ASTM D4704,ASTM D4705,ASTM D5733,ASTM D5734,ASTM D2207,ASTM D412,ASTM D638 ASTM D3137,ASTM D3574,ASTM D624,ASTM D3574,ASTM D4964,ASTM D2061,ASTM D5169,ASTM D5170,ASTM D2558,ASTM D413