



Dongguan Hust Tony Instruments Co.,Ltd
东莞华科东尼仪器有限公司

Addr: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: Addams@tonyhk.hk

ATG Torque Gauge



Toichi torque meter is measured manually, comparing the deformation of the measured object, the torque of the screw, and so on. Now it is also widely used in the camera industry, mainly to measure the torque of the camera lens when zooming.

Features:

1. Two-way operation lightweight torque gauge
2. The tip is a three-jawed chuck
3. The "push-lock button" makes it easy to secure the chuck
4. The dial is equipped with a stop at 270 degrees to prevent overload

High precision, strict quality

Addr: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: Addams@tonyhk.hk

Technical Parameter

Model	Without Memory Pointers	ATG045CN						
	With Memory Pointers	—	ATG09CN-S	ATG1.5CN-S	ATG3CN-S	ATG6CN-S	ATG12CN-S	ATG24CN-S
Torque Range [cN・m]	MIN.~MAX.	0.05~0.45	0.1~0.9	0.2~1.5	0.3~3	0.6~6	1~12	3~24
	Division value	0.01	0.02	0.02	0.05	0.1	0.2	0.5
Dimension [mm]	Dimension [mm]	L'	89					
	Diameter	D	43.5					
	Chuck Grip	Φd	1~6.5					
	Scale Dia.	D1	35					
	Body	L1	51					
Weight [kg]		0.5						
Accuracy		±2%						

