



Dongguan Hust Tony Instruments Co.,Ltd

东莞华科东尼仪器有限公司

Addr: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: Addams@tonyhk.hk

Tohnichi Torque Gauge BTG15CN-S



Toichi torque meter is measured manually, comparing the deformation of the measured object, the torque of the screw, and so on. Now it is also widely used in the camera industry, mainly to measure the torque of the camera lens when zooming.

Features:

1. Two-way operation lightweight torque gauge
2. The tip is a three-jawed chuck
3. The "push-lock button" makes it easy to secure the chuck
4. The dial is equipped with a stop at 270 degrees to prevent overload
5. High precision, strict quality



Dongguan Hust Tony Instruments Co.,Ltd
东莞华科东尼仪器有限公司

Addr: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: Addams@tonyhk.hk

Technical Parameter

Model		BTG 15CN-S	BTG 24CN-S_	BTG 36CN-S_	BTG 60CN-S	BTG 90CN-S	BTG 150CN-S_
		-					
Torque Range [cN·m]	MIN.~MAX.	2~15	3~24	4~36	6~60	10~90	20~150
	Division value	0.2	0.5		1		2
Dimension [mm]	Dimension [mm]	L'	119				
	Diameter	D	64.2				
	Chuck Grip	Φd	1~8.5				
	Scale Dia.	D1	53				
	Body	L1	67				
Weight [kg]		0.52					
Accuracy		±2%					

Notes

1. When measuring with the ATG/BTG (-S), be sure to clamp at least 10mm of the object to be measured inside the chuck.
2. Models 45ATG, ATG06Z and ATG045CN are only available without side and top memory pointers.

