

Address: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667 Email:

## Email: <u>Addams@tonyhk.hk</u>

## Ink Rub Tester HTZ-22-Manufactuer



Ink Rub Tester HTZ-22 Digital Ink Rub Tester applicable to the abrasion resistance test of surface coating layers of printed materials, e.g. ink layer or photosensitive (PS) coating.

It could effectively analyze the problems of poor abrasion resistance, ink layer falling off, lower printable force, and bad hardness of coating layers of printed materials. **Technical Specifications** 

Model	HTZ-22
Rub Pressure	908g, 1810g
Rub Speed	21,43,85,106r / min(optional)
Rub Area	50 * 100mm
Rub Times	0 – 999999
Machine Dimension	300×325×300cm
Power Supply	AC 220 V 50 Hz,40W
Net Weight	25Kg

## Feature

- 1.Wet and dry friction tests can be performed.
- 2.Our instrument can perform paper blur test, decolorization change test.
- 3. The instrument runs stably and the detection is accurate.
- 4. The operation is simple and easy to understand.

## Standards

GB 7706 ASTM F1571 ASTM F 2497