



Dongguan Hust Tony Instruments Co.,Ltd

东莞华科东尼仪器有限公司

Address: No. 1 Tech 9 Road, High - New Tech Development Zone, Songshan Lake, Dongguan City 523808, China

Tel: 86-769-23010657

Fax: 86-769-23010667

Email: Addams@tonyhk.hk

Leather Softness Tester HTX-022-Manufactuer-Hust Tony



Leather Softness Tester designed for softness testing in the leather industry.

The softness tester is used to test the softness of leather and animal skin by non-destructive method.

Determine whether the softness of the same batch of leather is uniform or the difference between different parts of a single piece of leather.

Leather softness tester is used to measure the softness of leather and animal skins to know whether the softness and hardness of the same batch of leather are uniform or not, or whether the softness and hardness of individual pieces of soft leather are different

Principle

This softness tester is an additional small pneumatic control valve to drive the force probe and clamp the leather to the base at the specified speed and pressure. The softness value is read by means of an indicator on the pressure arm.

Technical Specifications

| | | |
|-------------------------------|-----------------------------------------------|-------|
| Model | HTX-022 | |
| Testing Mode | Digital | |
| Load | 530±10g (small pneumatic control valve drive) | |
| Test Diameter | 20mm, 25mm optional | |
| Display meter Range | 0.1-10mm | |
| Overall Dimensions | 500×100×250mm (L×W×H) | |
| Net Weight | 5 kg | |
| Standard Configuration | Leather Softness Tester | 1 Set |
| | calibration disc | 1 Pcs |
| | Metal ring 20mm | 1 Pcs |
| | Metal ring 25mm | 1 Pcs |

- 1.Equipped with a high-precision digital display pressure gauge to provide accurate measurements, the measured value can be read directly.
- 2.Equipped with a large-capacity battery, there is no need to connect to a power outlet when using.
- 3.The compact size makes the instrument easy to carry and use anytime, anywhere.

Standard
IULTCS / IUP 36, ISO 17235